

APPLICATION: HOT WATER HEATER

FINDLAY CITY HEALTH DEPARTMENT

1644 TIFFIN AVENUE, SUITE A

FINDLAY OH 45840

TEL # (419) 424-7420 / Inspector's mobile tel # (419) 421-7860

Amount Paid _____ Date _____ City Permit No. _____

The undersigned hereby makes application for a permit for the installation of a device as herein specified, agreeing to do all such work in strict accordance with all applicable regulations.

Permit Address: _____

Owner: _____ Tel No. _____

-Building; new / old -Bldg to be used for: _____ -Completion Date: _____

1. Dialectic unions or non-conducting nipples should be used.
2. 3/4 inch copper or galvanized pipe must be installed in at least the first 12 inches. No CPVC, PVC allowed until at least 18 inches away from heater.
3. The outlet of a relief valve shall not be directly connected to the drainage system. Relief valve shall be piped full size above floor to an indirect receptor. The receptor must have a 1 1/2" drain or bigger and 2" air gap. Relief valve shall be discharged to the crawl space or to the outside of building. There shall be an air gap installed before or at the point of leaving the room.
4. Flue must rise vertically 12 inches before any turns or bends.
5. A pan will be installed in locations where leakage of the tank will cause damage. The water heater shall be installed in galvanized steel or other metal pan of equal corrosion resistance (min 24 gage). Electric water heaters shall be installed with a high-impact plastic pan of at least .625 inch thickness. The pan shall not be less than 1 1/2 inches deep or other pans conforming to the requirements of IAS 2-96. If the relief is indirected into pan, the drain must be 1 1/2 inches or bigger.
6. ANYWHERE flammable gases can be stored, the water heater must be elevated from the floor to the burner 18 inches.
7. Thermostats should be set at 115 to 120 degrees to avoid scalds. -And: Flue must rise to chimney. No level or downhill runs.
8. Gas cock must be within reach of gas valve. Gas line must have dirt leg. Coiled flex connectors do not constitute a dirt leg.
9. Electric water heaters shall have an electrical disconnect. A separate switch shall be provided to terminate the energy supplied to electric hot water heaters.

WATER HEATER - - - - - REPLACEMENT: \$ 25.00 (Circle One)

-FLUE: NATURAL POWER -FLUE SIZE: 3 4 5 6

-FUEL: NATURAL GAS PROPANE ELECTRIC

-GALLONS: _____ -MAKE: _____

OWNER -or-
CONTRACTOR: _____ R EG # _____

DATES OF INSPECTION: _____

SIGNATURE: _____

Rough: _____

Address: _____

Reinspection (\$25.00) _____

Final: _____

Telephone Number: _____

Final Approval Letter: _____